



**R R STONE**  
Solutions for Stone



A breathable impregnating sealer for all natural stones, tiles, grouts, concrete and wood surfaces

## DESCRIPTION

Ultima Seal is a breathable, impregnating seal for natural stone and wood surfaces. It repels dirt, making maintenance and cleaning much easier and impedes the formation of moulds and algae.

- Easy to apply
- Does not change the appearance and surface texture
- Suitable for indoor and outdoor use
- Protects against oil and water staining
- Inhibits damage due to efflorescence, salt staining
- Protects against freeze thaw damage and salt attack
- Controls mildew and algae growth



Ultima Seal

## PREPARATION

Surfaces to be treated should be clean and dry. If the surface has been treated with any other product before using ULTIMA SEAL this must be removed. Contact us for advice. Apply when surface temperature is between 5 - 35°C (40 - 95°F).

Application rate is approximately 8-20M<sup>2</sup> per litre per application, but this could vary depending on absorption.

Tests have shown that at least two applications are required on most stones.

Ultima Seal will not prevent surface etching damage from acids, scuff marks or wear and may darken or lighten some surfaces. Maintain with RR Stone's specially designed MAINTENANCE CLEANER and EVERYDAY WORKTOP CLEANER.

## HEALTH AND SAFETY

Ensure good ventilation when applying and drying. A vapour fumes mask should be worn in areas with poor ventilation. Wear gloves. Wash hands thoroughly after use. Keep away from drains, plants, water and soil.

Once cured, Ultima Seal is 'Food Safe'.

## INSTRUCTIONS



**Always test on a small area first**, this will give you an idea of the coverage and after 24 hours drying time, how the finish will look.

Do not thin down Ultima Seal.



Generously saturate the surface with Ultima Seal using an RR STONE SPONGE APPLICATOR, low-pressure hand spray, a clean brush, etc. Protect surrounding areas from drips and over-laps.



When Ultima Seal has soaked in, approx. 5 mins, gently polish the surface with a clean white dry cotton pad to remove excess seal. If the product has become sticky and more difficult to remove; moisten the cloth with Ultima Seal to ease polishing.



When the surface becomes touch dry, you should repeat steps above to improve protection.

When tiling, we recommend you apply one coat before and one after grouting.



Clean regularly. We recommend the use of RR Stone Maintenance Cleaner.

Do not walk on or otherwise make contact with the sealed surface until it is dry. The full protection takes 24-48 hours to develop, so you must be very careful to quickly remove all spillages within this time. Use a solvent (e.g. methylated spirits) to clean equipment.

## RECYCLING

Disposing of unused Ultima Seal is easy; just pour unused liquid into a bucket of old rags or absorbent soil or sand. (DO NOT POUR ONTO GROUND OR DOWN A DRAIN) leave to dry, then throw away in bin. DO NOT throw away bottles of liquid Ultima Seal. Plastic bottles can be recycled if all the sealant is removed and then containers are allowed to dry first.

RR Ultima Seal: Contains Trace Benzene

HARMFUL S2: KEEP OUT OF REACH OF CHILDREN.

S23 Do Not Breathe Fumes or Vapours. (WEAR MASK, VENTILLATE WELL)

S24 Avoid Contact with Skin. S46/62: If swallowed, do not induce vomiting, seek medical advice immediately and show this label. S29/35: Do not empty into drains; dispose of this material in a safe way. (see above), S-43 In case of fire use foam/dry powder/ CO2 - NEVER USE WATER.

R36/37: Irritating to Skin (WEAR GLOVES AND GOGGLES)

R65: May cause lung damage if swallowed. R66 Repeated exposure will have long term adverse effects in the aquatic environment.

*IMPORTANT: This information is provided for the guidance of prospective users: no liability, either express or implied, can be undertaken by the manufacturer - it is the responsibility of the intending user to determine fitness for purpose, although the manufacturers endeavour to ensure that the best advice and recommendations are given, based on laboratory and field experience. Liability is limited to replacement of materials found to be defective in materials or manufacture.*

R R Stone Co Ltd

Gatefoot Mill, Windermere Road,  
Staveley, Cumbria LA8 9PL

+44 (0) 1539 822666 [www.rrstone.co.uk](http://www.rrstone.co.uk)